

- A1
4. (Amended) A flow control valve according to claim 1, wherein said piston member includes a piston head, and said throttling orifice is defined between a downstream edge of said piston head and said non-uniform portion of the fluid flow passageway.

- A2
6. (Amended) A flow control valve according to claim 4, wherein the piston member includes a support structure, said support structure being mounted for sliding movement in the bore.

- A3
8. (Amended) A flow control valve according to claim 6, wherein the support structure includes a substantially axial fluid flow passageway.

9. (Amended) A flow control valve according to claim 6, wherein the support structure is engaged by a resilient biasing member.

10. (Amended) A flow control valve according to claim 1, including a housing in which the body member can be mounted, wherein said housing is capable of accommodating interchangeable flow control valve cartridges having different fluid flow capacities.

**Kindly insert the following new claims 12 - 20
into the application:**

12. A flow control valve according to claim 2, wherein said piston member includes a piston head, and said throttling orifice is defined between a downstream edge of said piston head and said non-uniform portion of the fluid flow passageway.
13. A flow control valve according to claim 3, wherein said piston member includes a piston head, and said throttling orifice is defined between a downstream edge of said piston head and said non-uniform portion of the fluid flow passageway.
14. A flow control valve according to claim 5, wherein the piston member includes a support structure, said support structure being mounted for sliding movement in the bore.
15. A flow control valve according to claim 7, wherein the support structure includes a substantially axial fluid flow passageway.
16. A flow control valve according to claim 7, wherein the support structure is engaged by a resilient biasing member.
17. A flow control valve according to claim 8, wherein the support structure is engaged by a resilient biasing member.

18. A flow control valve according to claim 2, including a housing in which the body member can be mounted, wherein said housing is capable of accommodating interchangeable flow control valve cartridges having different fluid flow capacities.

19. A flow control valve according to claim 3, including a housing in which the body member can be mounted, wherein said housing is capable of accommodating interchangeable flow control valve cartridges having different fluid flow capacities.

20. A flow control valve comprising:

a body member having a bore defining a fluid flow passageway;

a resiliently-biased piston member mounted in said passageway for movement relative to the body member in response to differential fluid pressure across the valve, said piston member defining an annular throttling orifice between said piston member and said bore, wherein at least a portion of said passageway has a non-uniform cross-section, such that a size of the annular orifice depends on a position of the piston member relative to the body member, said piston member comprising a side wall that cooperates with the non-uniform portion of the fluid flow passageway to define an annular fluid flow slot, said slot having a length and a cross-sectional area that depend on the position of the piston member relative to the body member.